This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

CLAIMS

1	1.	A dire	ect oxidation fuel cell system, comprising:		
2		(A)	a fuel source;		
3		(B)	a direct oxidation fuel cell, having:		
4			(i)	a me	mbrane electrode assembly, including;
5				(a)	a protonically conductive, electronically non-conductive
6					membrane electrolyte, having an anode face and an oppos-
7					ing cathode face; and
8				(b)	a catalyst coating disposed on each of said anode face and
9					said cathode face, whereby electricity-generating reactions
10					occur upon introduction of an associated fuel solution from
11					said fuel source including anodic dissociation of said fuel
12					solution into carbon dioxide, protons and electrons, and a
13					cathodic combination of protons, electrons and oxygen
14					from an associated source of oxygen, producing water; and
15			(ii)	an an	odic diffusion layer disposed in intimate contact with said an-
16				ode f	ace of said membrane electrode assembly and having a plu-
17				rality	of openings therein to allow said associated fuel solution to
18				pass	through to said anode face, as fuel is consumed at said anode;
19			(iii)	a catl	nodic diffusion layer disposed in intimate contact with said
20				catho	de face of said membrane electrode assembly and having a
21				plura	lity of openings therein to allow oxygen to pass through to
22				said (cathode face of said membrane electrode assembly;
23		(C)	a gas permeable layer comprised substantially of a gas permeable material,		
24			said gas permeable layer being disposed generally parallel to said anodic		
25			diffusion layer, such that said fuel solution can pass between said anodic		
26			diffusion layer and said gas permeable layer, and carbon dioxide that is		
27			releas	sed as f	uel is consumed at said anode face, passes through said gas
28			perm	eable la	yer and is vented from said fuel cell, whereby carbon dioxide
29			is ren	noved f	rom said fuel cell without active transport mechanisms; and

- gas permeable layera load coupled across said fuel cell, said load providing a path for said electrons whereby electricity is provided as said electricity-generating reactions proceed.
- 1 2. The direct oxidation fuel cell system as defined in claim 1 further comprising a
- 2 pressurized fuel delivery assembly coupled between said fuel source and said anodic dif-
- fusion layer in such a manner that as fuel is consumed at said anode face, and carbon di-
- 4 oxide is separated by said gas permeable layer, fuel is drawn into said fuel cell and said
- fuel cell is refilled by volume replacement from said fuel delivery assembly.
- 6
- 1 3. The direct oxidation fuel cell system as defined in claim 1 further comprising
- 2 means for evaporating off water produced at said cathode face of said protonically con-
- 3 ductive membrane.
- 1 4. The direct oxidation fuel cell system as defined in claim 1 wherein said gas per-
- 2 meable layer is comprised substantially of expanded PTFE.
- 5. The direct oxidation fuel cell system as defined in claim 1 wherein said gas per-
- 2 meable layer further includes a flow field channel formed therein to assist in the transport
- of liquids to said anode face of said protonically conductive membrane, while gases are
- 4 drawn through said gas permeable layer.
- 1 6. The direct oxidation fuel cell system as defined in claim 4 wherein said flow field
- channel is sealed with a material that is liquid impermeable, gas permeable, to resist
- passing of fuel through said gas permeable layer, by allowing gas to pass through to said
- 4 membrane.
- 7. The direct oxidation fuel cell system as defined in claim 1 further comprising a
- 2 housing encapsulating said direct oxidation fuel cell, said housing having an inlet port for
- 3 the introduction of fuel into said fuel cell.

- 1 8. The direct oxidation fuel dell system as defined in claim 6 further comprising a
- second port being defined in said housing into which fuel can be introduced, or removed,
- 3 from the fuel cell.
- 1 9. The direct oxidation fuel cell system as defined in claim 1 wherein said protoni-
- 2 cally conductive membrane is comprised substantially of Nafion.
- 1 10. The direct oxidation fuel cell system as defined in claim 1 wherein said fuel from
- 2 said fuel source is a methanol solution.
- 1 11. The direct oxidation fuel cell system as defined in claim 1 wherein said anodic
- diffusion layer is sandwiched between said gas permeable layer and said protonically-
- 3 conductive membrane.
- 1 12. The direct oxidation fuel cell system as defined in claim 1 wherein said gas sepa
- ration membrane is in intimate contact with said anodic diffusion layer.
- 1 13. The direct oxidation fuel cell system as defined in claim 7 wherein said gas per-
- 2 meable layer is disposed on a portion of said housing, encompassing said anode chamber.
- 14. The direct oxidation fuel cell system as defined in claim 11 wherein said gas per-
- 2 meable layer is disposed on at least one surface of said housing.
- 15. The direct oxidation fuel cell system as defined in claim 11 wherein said gas per-
- 2 meable layer comprises at least one porthole in said housing.
- 1 16. A direct oxidation fuel cell, comprising:
- 2 (A) a membrane electrode assembly, including:

3

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

- (i) a protonically conductive, electronically non-conductive membrane electrolyte, having an anode face and an opposing cathode face; and
- (ii) a catalyst coating disposed on each of said anode face and said cathode face, whereby electricity-generating reactions occur upon introduction of fuel solution from an associated fuel source, including anodic dissociation of said fuel solution into carbon dioxide, protons and electrons, and cathodic combination of protons, electrons and oxygen from an associated source of oxygen, producing water.
- (B) an anodic diffusion layer disposed in intimate contact with said anode face of said membrane electrode assembly, and having a plurality of openings therein to allow said associated fuel mixture to pass through to said anode face as fuel is consumed at said anode;
- (C) a cathodic diffusion layer disposed in intimate contact with said cathode face of said membrane electrode assembly and having a plurality of openings therein to allow oxygen to pass through to said cathode face of said membrane electrode assembly; and
- (D) a gas permeable, fluid impermeable membrane disposed generally parallel to said anodic diffusion layer, such that said fuel solution can pass between said anodic diffusion layer and said gas permeable membrane to separate carbon dioxide that is released at said anode face and to vent carbon dioxide from said fuel cell, whereby carbon dioxide is removed from said fuel cell without active transport mechanisms.
- 17. The direct oxidation fuel cell as defined in daim 16 wherein said gas permeable membrane is comprised substantially of expanded PFFE.
- 1 18. The direct oxidation fuel cell as defined in claim 17 wherein said gas permeable
 2 membrane includes a flow field channel to assist in the transport of liquids across said
 3 anode face of said protonically conductive membrane, while gases are drawn through
- 4 said gas permeable membrane.

3

10

11

12

13

14

15

16

- 1 19. The direct oxidation fuel cell as defined in claim 18 wherein said flow field chan-
- 2 nel is sealed with a material that is liquid impermeable to resist passing of fuel through
- 3 said gas permeable layer.
- 20. A fuel container and delivery assembly for use with an associated direct oxidation
- fuel cell system, the fuel container and delivery assembly, comprising:
 - (A) an exterior housing having an opening at one end thereof;
 - (B) a first inner container disposed within said exterior housing, for holding a fuel solution, and a fuel conduit extending through said opening in said exterior housing, and coupling said first inner container to said associated fuel cell system;
 - (C) a second inner container disposed within said exterior housing, for holding water to be mixed with said fuel solution and a water conduit extending through said opening in said exterior housing, and coupling said second inner container to said associated fuel cell system;
 - (D) an interface for sealing the coupling of said fuel conduit and said water conduit with said associated fuel cell system;
 - (E) mixing assembly connecting said fuel conduit with said water conduit to mix fuel and water to adjust an amount of water mixed into fuel to result in a fuel mixture of a predetermined concentration; and
- 17 (F) delivery conduit for transporting said resulting fuel mixture to said associ-18 ated direct oxidation fuel cell system.
- 1 21. The fuel container and delivery assembly as defined in claim 20 wherein said fuel
- 2 conduit is constructed to intersect into said water conduit to thereby mix said fuel solu-
- 3 tion with water.
- 1 22. The fuel container and delivery assembly as defined in claim 21 further compris-
- ing a valve located along said fuel conduit to control the addition of fuel solution to be
- 3 mixed with said water.

- 1 23. The fuel container and delivery assembly as defined in claim 20 wherein said
- water conduit is constructed to intersect into said fuel conduit to thereby mix water into
- 3 said fuel solution.
- 1 24. The fuel container and delivery assembly as defined in claim 23 further compris-
- 2 ing a valve located along said water conduit to control the addition of water to be mixed
- 3 into said fuel solution.
- 1 25. The fuel container and delivery assembly as defined in claim 20 further compris-
- ing a mixing chamber into which said fuel conduit and said water conduit lead to thereby
- mix said fuel solution and said water.
- 1 26. The fuel container and delivery assembly as defined in claim 25 further compris-
- ing a valve located along at least one of said fuel conduit and said water conduit to con-
- trol the flow of liquids into said mixing chamber.
- 1 27. The fuel container and delivery assembly as defined in claim 26 further compris-
- 2 ing a valve located along said delivery conduit to control the flow of the resulting fuel
- mixture to said associated direct oxidation fuel cell system.
- 1 28. The fuel container and delivery assembly as defined in claim 27, wherein said fuel
- 2 conduit and said water conduit include openings along walls thereof, and said walls of
- said fuel conduit and said water conduit are disposed configuous to said anode diffusion
- layer, which in turn is in intimate contact with said anode face of said fuel cell, whereby

- fuel and water are dispersed through said walls of said conduits to said anode diffusion
- 6 layer.
- 1 29. The fuel container and delivery assembly as defined in claim 28 wherein said fuel
- 2 conduit and said water conduit include means for controlling the amount of each sub-
- stance that travels through its respective conduit to thereby control the fuel concentration
- of liquids presented to said anode face of said fuel cell.
- 1 30. The fuel container and delivery assembly as defined in claim 20 wherein said as-
- sociated fuel cell includes a gas permeable layer disposed generally parallel to said ano-
- dic diffusion layer, said gas permeable layer removing carbon dioxide from said fuel cell.
- 1 31. The fuel container and delivery assembly as defined in claim 30 wherein said gas
- 2 permeable layer is comprised substantially of expanded PTFE.
- 1 32. The fuel container and delivery assembly as defined in claim 30 wherein said fuel
- cell includes means for evaporating off water produced at said cathode face of said mem-
- 3 brane electrode assembly.
- The fuel container and delivery assembly as defined in claim 20 wherein said ex-
- terior housing includes a pressure-applying element which applies pressure to at least one
- of said fuel container and said water container to place liquids in said fuel conduit and
- 4 said water conduit under pressure.
- 1 34. The fuel container and delivery assembly as defined in daim 20 further compris-
- 2 ing a pump to transport liquid fuel from said fuel container into said fuel conduit.

- 35. The fuel container and delivery assembly as defined in claim 20 further compris-
- ing a pump to transport water from said water container into said water conduit.
- 1 36. A method of removing carbon dioxide from a direct oxidation fuel cell, said fuel
- cell having a protonically conductive membrane, said protonically conductive membrane
- having an anode, and an anode diffusion layer, and a cathode, the method including the
- 4 steps of:

5

separating carbon dioxide from said anode by providing a gas permeable layer, comprised substantially of a gas permeable, liquid impermeable material contiguous to an anodic diffusion layer, which is in turn, in intimate contact with said protonically conductive membrane allowing removal of carbon dioxide generated at said anode, and while allowing fuel solution to penetrate to said anode.

